









Miniature Circuit Breakers - Series E90SUC 6kA - EN60898					(for universal current)		
6000	In (A)	Ue (V DC)	Umax (V)	Tripping characteristic B (3=5)xIn		Tripping characteristic C (5=10)xIn	
				Cat. No.	Ref. No.	Cat. No.	Ref. No.
1P - 1 Module							
	0,5	250				E91SUCC0.5	553304
	1	250				E91SUCC01	553305
	2	250				E91SUCC02	553306
	3	250				E91SUCC03	553307
	4	250				E91SUCC04	553308
	6	250		E91SUCB06	553271	E91SUCC06	553309
	10	250		E91SUCB10	553273	E91SUCC10	553311
	13	250		E91SUCB13	553274	E91SUCC13	553312
	16	250		E91SUCB16	553275	E91SUCC16	553313
	20	250		E91SUCB20	553276	E91SUCC20	553314
	25	250		E91SUCB25	553277	E91SUCC25	553315
	32	250		E91SUCB32	553278	E91SUCC32	553316
	40	250		E91SUCB40	553279	E91SUCC40	553317
	50	250		E91SUCB50	553280	E91SUCC50	553318
63	250		E91SUCB63	553281	E91SUCC63	553319	
Isolator application according to EN 60947-2							
2P - 2 Modules							
	0,5	250 - 440	500			E92SUCC0.5	553320
	1	250 - 440	500			E92SUCC01	553321
	2	250 - 440	500			E92SUCC02	553322
	3	250 - 440	500			E92SUCC03	553323
	4	250 - 440	500			E92SUCC04	553324
	6	250 - 440	500	E92SUCB06	553290	E92SUCC06	553325
	10	250 - 440	500	E92SUCB10	553292	E92SUCC10	553327
	13	250 - 440	500	E92SUCB13	553293	E92SUCC13	553328
	16	250 - 440	500	E92SUCB16	553294	E92SUCC16	553329
	20	250 - 440	500	E92SUCB20	553295	E92SUCC20	553330
	25	250 - 440	500	E92SUCB25	553296	E92SUCC25	553331
	32	250 - 440	500	E92SUCB32	553297	E92SUCC32	553332
	40	250 - 440	500	E92SUCB40	553298	E92SUCC40	553333
	50	250 - 440	500	E92SUCB50	553299	E92SUCC50	553334
63	250 - 440	500	E92SUCB63	553300	E92SUCC63	553335	
Isolator application according to EN 60947-2							
4P - 4,5 Modules							
	10	440 - 880	1000	E94SUCB10	691213		
	13	440 - 880	1000				
	16	440 - 880	1000	E94SUCB16	691214		
	20	440 - 880	1000	E94SUCB20	691215		
	25	440 - 880	1000				
	32	440 - 880	1000				
	40	440 - 880	1000	E94SUCB40	691216		
	63	440 - 880	1000	E94SUCB63	691217		
Isolator application according to EN 60947-2							

Electrical drawings - Series E90SUC	E91SUC 1P		E92SUC 2P		E94SUC 4P	
Maximum voltage between the poles	250V ==	250V ==	440V ==	440V ==	440V == max 6kA	880V == max 6kA
Maximum voltage between poles and ground	250V ==	250V ==	440V ==	440V ==	250V ==	
Supply from lower terminals						
Supply from upper terminals	