







Comfort Functions - Misurament Instruments						
	Catalogue number	Description	Supply	Numer of modules	Reference number	
Misurament Instruments						
Network monitor (without energy measurement)						
	E8F/4	Three-phase + Neutral o Three-phase, Current, Voltage, phase active or reactive power, active reactive and apparent power, cosφ, neutral corrent, working hour and minute, power demand and power max demand	115... 230V AC	4	852210	
Network monitor						
	E8MF/4	Three-phase + Neutral o Three-phase, Current, Voltage, phase active or reactive power, active reactive and apparent power, cosφ, neutral corrent, frequency, working hour and minute, power demand and power max demand, phase sequence	115... 230V AC	4	852198	
	E8MF/4RS	as E8MF/4 with RS485 communication, Jbus/Modbus	115... 230V AC	4	852199	
	E8MF/4I	as E8MF/4 with pulse output for energy counting	115... 230V AC	4	852201	
Energy counter						
	E8W/1-1	Single-phase, direct connection up to 32A, active energy, backlit display	Selfsupplied	1	852206	
	E8W1-63	Single-phase, direct connection up to 63A, total or partial active energy (reset), Current, Voltage, display 6 digit, sealable housing	Selfsupplied	2	852203	
	E8W4-63	Three-phase + Neutral o Three-phase, direct connection up to 63A, total or partial active energy (reset), pulse output, active power max. demand, energy count with double tariff, display 8 digit, sealable housing	Selfsupplied	4	852204	
	E8W4-4	Three-phase + Neutral o Three-phase, connection on TA/1A and 5A, total or partial active energy (reset), pulse output, active power max. demand, energy count with double tariff, display 8 digit, sealable housing	Selfsupplied	4	852205	
Digital Ammeter/Volt meter						
	E8AV/D	Alternating voltage or current selectable measurement, 1000 display points, direct connection ammeter on TA/1A or 5A, direct connection volmeter up to 500V	230V AC	4	852092	
Analogue Voltmeter						
	E8A/50	Moving iron equipment, direct connection, scale 0...50A, class 1,5, working frequency 45...65Hz	Selfsupplied	3	851173	
	E8A/60	Moving iron equipment, direct connection, scale 0...60A, class 1,5, working frequency 45...65Hz	Selfsupplied	3	851176	
	E8A/1000	Moving iron equipment, connection on TA/5A, without scale, class 1,5, working frequency 45...65Hz	Selfsupplied	3	851196	
Analogue Ammeter						
	E8V/500	Moving iron equipment, direct connection up to 500V, class 1,5, working frequency 45...65Hz	Selfsupplied	3	851193	

Comfort Functions - Misurament Instruments

	Catalogue number	Description	Rated burden	Numer of modules	Reference number		
Misurament Instruments							
	Switch E8CV/4	Voltmetric 4 position switch 3 Linked voltage (12A - 690V)		3	852195		
	E8CV/7	Voltmetric 7 position switch 3 Linked voltage , 3 Phase-neutral (12A - 690V)		3	852196		
	E8CA/4	Single pole 4 position Ammetric switch 4 for 3TA (12A - 690V)		3	852197		
	Interchange Ammeter scaleplates for E8A/1000						
	E8A/15S	0... 15A			851273		
	E8A/20S	0... 20A			851274		
	E8A/25S	0... 25A			851275		
	E8A/40S	0... 40A			851276		
	E8A/50S	0... 50A			851280		
	E8A/60S	0... 60A			851281		
	E8A/80S	0... 80A			851282		
	E8A/100S	0... 100A			851283		
	E8A/150S	0... 150A			851284		
	E8A/200S	0... 200A			851285		
	E8A/250S	0... 250A			851286		
	E8A/300S	0... 300A			851287		
	E8A/400S	0... 400A			851288		
	E8A/500S	0... 500A			851289		
E8A/600S	0... 600A			851290			
E8A/800S	0... 800A			851291			
E8A/1000S	0... 1000A			851292			
	Current transformer						
	E8T/15	15/5A	wound primary	2VA cl. 0,5	852096		
	E8T/25	25/5A	wound primary	2VA cl. 0,5	852098		
		E8T/40	40/5A	hole Ø 21mm	1VA cl. 3	852099	
			E8T/50	50/5A	hole Ø 22mm	2VA cl. 3	852100
			E8T/60	60/5A	hole Ø 22mm	2,5VA cl. 3	852101
	E8T/80		80/5A	hole Ø 22mm	3VA cl. 3	852102	
	E8T/100		100/5A	hole Ø 22mm	2VA cl. 1	852103	
	E8T/150		150/5A	hole Ø 22mm	2VA cl. 0,5	852104	
		E8T/200	200/5A	hole Ø 22mm	3VA cl. 0,5	852105	
		E8T/250	250/5A	hole Ø 22mm	5VA cl. 0,5	852106	
		E8T/300	300/5A	hole Ø 32mm (window 10,5 x 40,5mm)	5VA cl. 0,5	852107	
		E8T/400	400/5A	hole Ø 32mm (window 10,5 x 40,5mm)	8VA cl. 0,5	852108	
		E8T/500	500/5A	hole Ø 32mm (window 10,5 x 40,5mm)	10VA cl. 0,5	852109	
		E8T/600	600/5A	hole Ø 32mm (window 10,5 x 40,5mm)	12VA cl. 0,5	852110	
	E8T/800	800/5A	window 12,5 x 51mm	8VA cl. 0,5	852111		
	E8T/1000	1000/5A	window 12,5 x 51mm	10VA cl. 0,5	852112		